

AUTOTROL® 760 TIMER

SIMPLE ECONOMIC ELECTRONIC METER CONTROL





FEATURES/BENEFITS

LCD display alternates between time of day and volume remaining

Large LCD display for simplified programming

Time of day super capacitor backup for power loss

Queued regeneration is indicated by a flashing icon

Easy installation with plug-in wiring harnesses

Easy electronic programming

Displays regeneration step and time remaining during regeneration

Programming stored in memory and will not be lost due to power outages

Adjustable Time of Regeneration

History

- Initial Setting Value
- Days since last regeneration
- Current Flow Rate
- Water used today since Time of Regeneration
- Water used since last regeneration

Timer wall mount kits

OPTIONS

7

UL recognized to the 979



Restriction of Hazardous Substance Compliant

• Total water used since reset

- Average usage for each day of week
- Average service cycle
- Peak Flow Rate
- Day and Time of Peak Flow Rate
- Months since service
- Water used since last regeneration
- Number of regenerations since last serviced

System capacity and cycle step are calculated by the controller.

12- volt AC operation

Filter or conditioner control

Calendar override

28- day variable reserve



FILTRATION & PROCESS 5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209 P: 262.238.4400 | F: 262.238.4404 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

4003062 REV B MR14 © 2014 Pentair Residential Filtration, LLC. All Rights Reserved.