

GRO-575 5-Stage Reverse Osmosis System

McKay's
ESTD CO. 1927

Celebrating 97 years!

OVERVIEW

This system includes 5 unique filtration stages and features a patented Diamond Flow technology that work together to reduce a broad range of contaminants and impurities found in your home water before polishing it off to give you better tasting water – water that wows. Enjoy peace of mind knowing this system reduces up to 98% of PFOA/PFOS “forever chemicals”. This system is certified by IAPMO R&T against NSF/ANSI 53 for the reduction of perfluorooctanoic acid (PFOA) and perfluorooctane sulfonate (PFOS). It is recommended that the filter cartridges be replaced every 12 months.



Manufactured by Pentair

BEST WATER USAGE



Drinking Water



Washing Fruits & Vegetables



Cooking & Boiling Water



Water for Pets



Water for Plants & Flowers



Water for Coffee or Tea

This Reverse Osmosis System produces less water waste than other reverse osmosis systems in the market.

FEATURES

- Save money and drink water by eliminating the need for bottled water
- High efficiency GRO 75 GPD membrane technology
- Effortless click-in lock cartridge installation
- 3/8" push fit plumbing connection for easy installation and high flow
- Water supply valve shut off fits multiple piping styles
- Includes high performance VOC carbon block filters
- Color coded cartridges to maintain proper filter sequence
- Lead, chemical and VOC reduction cartridge
- 3/8" tubing to storage tank and faucet
- Built-in check valve with multi-point backflow protection
- Utilizes the dual technology of the DFX Diamond Flow series combining a sediment and carbon block in one cartridge
- Faucet with air gap included



MODEL GRO-575

Parts Included:

- System with cartridges
- Storage Tank
- Installation Hardware Kit
- Lead-free drinking water faucet with air gap



Contaminant Reduction: Chlorine Taste and Odor, Nominal Particulate, Class I, Atrazine, Lead, Lindane, Chloroform, Arsenic (Pentavalent) <= 50 ppb, Barium, Cadmium, Chromium (Hexavalent), Chromium (Trivalent), Copper, Fluoride, Radium 226/228, Selenium, Turbidity, TDS, VOC'S, PFOA/PFOS, Cyst: NSF/ANSI Standards 53 and 58 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means.

SPECIFICATIONS

Temperature Range:	40-100F (4.4-37.8C)	Efficiency Rating:	23.57%
Pressure Range:	40-100 psi (2.75-6.89 bar)	TDS Rejection:	96.3%
System Production Rate:	21.08 gpd (79.77 Lpd)	Dimensions:	17.82"W x 5.46"D x 12.54"H
Recovery Rating:	41.05%	Weight:	810.7 lbs (4.8 kg) system only