

Pentair FreshPoint F3000 Under Counter Filtration System

McKay's
ESTD CO. 1927

Celebrating 97 years!

OVERVIEW

Put dirty water in the past and transform your water into clearer, more refreshing water with the turn of your tap. This product features a set of twin carbon blocks with lead reduction media to reduce more than 60 contaminants, like chlorine, lead, cysts, and volatile organic compounds (VOCs).



Manufactured by Pentair

3-STAGE FILTER BENEFITS



No more expensive plastic bottled water



Unlimited water on tap



No harmful chemical additives



Zero water waste



Cleaner and refreshing water



Easy to install with dedicated side faucet

3-stage filtration to reduce heavy sediment and 60+ contaminants from your water.

FEATURES

- Comes ready to install with dedicated side faucet
- Effortless click-in installation that saves you time
- Color-coded cartridges make filter change-outs simple and hassle-free
- Zero waste water
- Uses no harmful chemical additives to give you a higher quality of water
- 3-stage filtration to reduce heavy sediment and 60+ contaminants from your water
- Double o-ring design for optimal cartridge sealing and leak protection
- Optional filter life monitor will notify you when it's time to replace the cartridge (Model F3000-B2M only)



MODEL F3000

Parts Included:

- Side faucet
- Installation kit
- Installation and operation manual
- Filter System with Cartridge

Magnetic Cartridge Timer

Signals Filter Replacement

Color Coded Cartridges

Maintains Proper Filter Sequence

High Power Magnet Mounded Cover

For Ease of Installation

Built-in Check Valve System

Providing Multi-Point Backflow Protection



Faucet Included

Contaminant Reduction: Chlorine Taste & Odor, Lead, Atrazine, Lindane, Nominal Particulate, Class I, VOC's, PFOA/PFOS, Cyst: NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means.

SPECIFICATIONS

Temperature Range:	40 - 100°F (4.4 - 37.8°C)	Capacity	675 Gallons (2555 Liters)
Pressure Range:	40-100 psi (2.75-6.89 bar)	Filter Life:	Up to 1 Year
System Production Rate:	0.60 gpd (2.27 Lpd)	Dimensions:	12.5" H X 11.25" W X 5.46" D
Inlet Size:	3/8" QC	Weight:	6 lbs